


AGT GERMAN TECHNICS

Industrial Components and Equipment

Rectangular profiles
Hot Rolled DIN EN 10210




a mm	b mm	t mm	Theoretical Wt. kg/m
40	20	2.0	1.68
40	20	2.5	2.03
40	20	3.0	2.36
50	30	2.0	2.31
50	30	2.5	2.82
50	30	3.0	3.30
50	30	4.0	4.20
60	40	2.0	2.93
60	40	2.5	3.60
60	40	3.0	4.25
60	40	4.0	5.45
60	40	5.0	6.56
70	50	2.0	3.56
70	50	2.5	4.39
70	50	3.0	5.19
70	50	4.0	6.71
70	50	5.0	8.13
80	40	2.0	3.56
80	40	2.5	4.39
80	40	3.0	5.19
80	40	4.0	6.71
80	40	5.0	8.13
80	60	2.0	4.19
80	60	2.5	5.17
80	60	3.0	6.13
80	60	4.0	7.97
80	60	5.0	9.70
90	50	2.0	4.19
90	50	2.5	5.17
90	50	3.0	6.13
90	50	4.0	7.97
90	50	5.0	9.70
100	40	2.5	5.17
100	40	3.0	6.13
100	40	4.0	7.97
100	40	5.0	9.70
100	50	2.5	5.56
100	50	3.0	6.60
100	50	4.0	8.59
100	50	5.0	10.50
100	50	6.0	12.30

a mm	b mm	t mm	Theoretical Wt. kg/m
100	50	6.3	12.50
100	60	2.5	5.96
100	60	3.0	7.07
100	60	4.0	9.22
100	60	5.0	11.30
100	60	6.0	13.20
100	60	6.3	13.50
100	80	2.5	6.74
100	80	3.0	8.01
100	80	4.0	10.50
100	80	5.0	12.80
100	80	6.0	15.10
100	80	6.3	15.50
120	60	2.5	6.74
120	60	3.0	8.01
120	60	4.0	10.50
120	60	5.0	12.80
120	60	6.0	15.10
120	60	6.3	15.50
120	60	8.0	18.90
120	60	3.0	8.96
120	80	4.0	11.70
120	80	5.0	14.40
120	80	6.0	17.00
120	80	6.3	17.50
120	80	8.0	21.40
140	80	4.0	13.00
140	80	5.0	16.00
140	80	6.0	18.90
140	80	6.3	19.40
140	80	8.0	23.90
150	100	4.0	14.90
150	100	5.0	18.30
150	100	6.0	21.70
150	100	6.3	22.40
150	100	8.0	27.70
150	100	10.0	33.40
150	100	12.0	37.70
150	100	12.5	38.90
160	80	4.0	14.20
160	80	5.0	17.50

AGT GERMAN TECHNICS

Industrial Components and Equipment

Rectangular profiles Hot Rolled DIN EN 10210



a mm	b mm	t mm	Theoretical Wt. kg/m
160	80	6.0	20.70
160	80	6.3	21.40
160	80	8.0	26.40
160	80	10.0	31.80
160	80	12.0	35.80
160	80	12.5	36.90
180	100	4.0	16.80
180	100	5.0	20.70
180	100	6.0	24.50
180	100	6.3	25.40
180	100	8	31.40
180	100	10	38.10
180	100	12	43.40
180	100	12.5	44.80
200	100	4.0	18.00
200	100	6.0	26.40
200	100	6.3	27.40
200	100	8.0	33.90
200	100	10.0	41.30
200	100	12.0	47.10
200	100	12.5	48.70
200	120	4.0	19.30
200	120	5.0	23.80
200	120	6.0	28.30
200	120	6.3	29.30
200	120	8.0	36.50
200	120	10.0	44.40
200	120	12.0	50.90
200	120	12.5	52.60
250	150	5.0	30.10
250	150	6.0	35.80
250	150	6.3	37.20
250	150	8.0	46.50
250	150	10.0	57.00
250	150	12.0	66.00
250	150	12.5	68.30
250	150	16.0	83.80
260	180	5.0	33.20
260	180	6.0	39.60
260	180	6.3	41.20
260	180	8.0	51.50
260	180	10.0	63.20

a mm	b mm	t mm	Theoretical Wt. kg/m
260	180	12.0	73.50
260	180	12.5	76.20
260	180	16.0	93.90
300	100	6.0	35.80
300	100	6.3	37.20
300	100	8.0	46.50
300	100	10.0	57.00
300	100	12.0	66.00
300	100	12.5	68.30
300	100	16.0	83.80
300	150	6.0	40.50
300	150	6.3	42.20
300	150	8.0	52.80
300	150	10.0	64.80
300	150	12.0	75.40
300	150	12.5	78.10
300	150	16.0	96.40
300	200	6.0	45.20
300	200	6.3	47.10
300	200	8.0	59.10
300	200	10.0	72.70
300	200	12.0	84.80
300	200	12.5	88.00
300	200	16.0	109.00
350	250	6.0	54.70
350	250	6.3	57.00
350	250	8.0	71.60
350	250	10.0	88.40
350	250	12.0	104.00
350	250	12.5	108.00
350	250	16.0	134.00
400	200	8.0	71.60
400	200	10.0	88.40
400	200	12.0	104.00
400	200	12.5	108.00
400	200	16.0	134.00
400	300	8.0	84.20
400	300	10.0	104.00
400	300	12.0	123.00
400	300	12.5	127.00
400	300	16.0	159.00