


AGT GERMAN TECHNICS

Industrial Components and Equipment

UNP Beams

Hot Rolled DIN 1026

Normal Length 6 - 15 m



Sizes mm	h	b	t_s	$t_g = r_1$	r_2	Area cm ²	Theoretical Wt. kg/m
30x15	30	15	4	4.5	2	2.21	1.79
30	30	33	5	7	3.5	5.44	4.40
40x20	40	20	5	5.5	2.5	3.66	2.96
40	40	35	5	7	3.5	6.21	5.02
50x25	50	25	5	6	3	4.92	3.98
50	50	38	5	7	3.5	7.12	5.76
60x30	60	30	6	6	3	6.46	5.22
65	65	42	5.5	7.5	4	9.03	7.30
80	80	45	6	8	4	11.0	8.9
100	100	50	6	8.5	4.5	13.5	10.9
120	120	55	7	9	4.5	17.0	13.7
140	140	60	7	10	5	20.4	16.4
160	160	65	7.5	10.5	5.5	24.0	19.3
180	180	70	8	11	5.5	28.0	22.5
200	200	75	8.5	11.5	6	32.2	26.0
220	220	80	9	12.5	6.5	37.4	30.0
240	240	85	9.5	13	6.5	42.3	34.0
260	260	90	10	14	7	48.3	39.0
280	280	95	10	15	7.5	53.3	43.0
300	300	100	10	16	8	58.8	48.0
320	320	100	14	17.5	8.75	75.8	61.0
350	350	100	14	16	8	77.3	62.0
380	380	102	13.5	16	8	80.4	65.0
400	400	110	14	18	9	91.5	74.0

UNP,Angles,Tol4830